

VINTAGE RICHFIELD®




When an aged, weathered texture is important, our Vintage Richfield® pavers offer a timeless appearance that looks like it's been installed for years. Available in three sizes, our Vintage Richfield® pavers have a non-dimpled texture and can be used to create unique and interesting patterns for any application.



DesignPAVE®

PREMIUM
CONCRETE
PAVERS

PRODUCT SPECS



- a) Vintage Richfield® Small Square – 5 1/2" x 5 1/2"
- b) Vintage Richfield® Square – 8 3/16" x 8 3/16"
- c) Vintage Richfield® Standard Rectangle – 8 1/4" x 5 1/2"
- d) Vintage Richfield® Large Rectangle – 11" x 8 1/4"

All Vintage Richfield® pavers are 2 3/4" thick


APPLICATIONS

Urban street parking, entrance areas, porte caches, crosswalks, esplanades, light duty parking lots, residential driveways, patios, walkways, pedestrian malls, medians, terraces, pool decks, sidewalks, garden paths, roof gardens

COMPOSITION AND MANUFACTURE

Vintage Richfield® pavers are made from a "no slump" concrete mix. Made under extreme pressure and high frequency vibrations, Vintage Richfield® pavers have an average compression strength greater than 8000psi, a water absorption maximum of 5% and will meet or exceed ASTM C-936 and freeze-thaw testing per section 8 of ASTM C-67.

INSTALLATION PATTERNS



3 Piece Random
51% Standard Rec.
11% Large Rec.
38% Small Sq.

Muster D
40% Small Sq.
60% Standard Rec.

Muster K
72% Standard Rec.
28% Small Sq.

Running Bond
Standard Rec.,
Small Rec., or
Small Sq.

INSTALLATION

1. Excavate unsuitable, unstable or unconsolidable subgrade material and compact the area which has been cleared. Backfill and level with dense graded aggregate suitable for use material (typically 4-6 in. of compacted base for light vehicular and pedestrian traffic) or as otherwise directed by Site Engineer/Architect/Landscape Architect.
2. Place bedding course of washed sand conforming to the grading requirements of ASTM C-33 to a maximum uniform depth of 1-1 1/2 in. (25-38mm) screeded to the grade and profile required.
3. Install Vintage Richfield® Pavers with joints approximately 1/8 in. (3mm).
4. Where required, cut pavers with an approved cutting device to fit accurately, neatly and without damaging edges.
5. Tamp pavers with a plate compactor, uniformly level, true to grade and free of movement.
6. Spread sand to 1/8 inch (3mm) thickness over entire paving area.
7. Make one more pass with plate compactor to fill joints with sand.

Complete installation and specification details are available by contacting your Oberfields Sales Representative.

PACKAGING INFO

PRODUCT	WEIGHT PER SQ. FT.	UNITS PER SQ. FT.	UNITS PER BAND	UNITS PER CUBE	WEIGHT PER CUBE	SQ. FT. PER UNIT	SQ. FT. PER BAND	SQ. FT. PER CUBE	COLORS STOCKED
Small Square	32.0	4.76	48	384	2592	0.21	10.08	81	Canyon Creek, Charcoal, Earth, Flagstone
Square	27.6	2.35	40	216	2815	0.43	17.00	102	Canyon Creek, Charcoal, Earth, Flagstone
Standard Rectangle	32.0	3.17	48	288	1912	0.32	15.36	91	Canyon Creek, Charcoal, Earth, Flagstone
Large Rectangle	27.6	N/A	N/A	318	1380	Varies	N/A	50	Canyon Creek, Charcoal, Earth, Flagstone