

ROSETTA[®] DIMENSIONAL FLAGSTONE



Rosetta[®] Dimensional Flagstone mimics an authentic, slate texture using six unique shapes and various stone textures. It's the perfect choice for walkways and elegant patios that require consistent dimensions and a more formal, sophisticated look.




Design PAVE[®]

PREMIUM
CONCRETE
PAVERS

ROSETTA® DIMENSIONAL FLAGSTONE

DesignPAVE®

PRODUCT SPECS



- a) Rosetta® Dimensional Flagstone* – 6" x 12"
- b) Rosetta® Dimensional Flagstone* – 12" x 12"
- c) Rosetta® Dimensional Flagstone* – 12" x 18"
- d) Rosetta® Dimensional Flagstone* – 18" x 18"
- e) Rosetta® Dimensional Flagstone* – 18" x 24"
- f) Rosetta® Dimensional Flagstone* – 24" x 24"

All Dimensional Flagstone are 2" thick


APPLICATIONS

Urban street parking, entrance areas, porte caches, crosswalks, esplandes, light duty parking lots, residential driveways, patios, walkways, pedestrian malls, medians, terraces, pool decks, sidewalks, garden paths, roof gardens

COMPOSITION AND MANUFACTURE

Rosetta® Dimensional Flagstone pavers are made from a "no slump" concrete mix. Made under extreme pressure and high frequency vibrations, Rosetta® Dimensional Flagstone pavers have an average compression strength greater than 8000psi, a water absorption maximum of 5% and will meet or exceed ASTM C-936 and freeze-thaw testing per section 8 of ASTM C-67.

INSTALLATION PATTERNS



INSTALLATION

1. Excavate unsuitable, unstable or unconsolidable subgrade material and compact the area which has been cleared. Backfill and level with dense graded aggregate suitable for use material (typically 4-6 in. of compacted base for light vehicular and pedestrian traffic) or as otherwise directed by Site Engineer/Architect/Landscape Architect.
2. Place bedding course of washed sand conforming to the grading requirements of ASTM C-33 to a maximum uniform depth of 1-1 1/2 in. (25-38mm) screeded to the grade and profile required.
3. Install Rosetta® Dimensional Flagstone Pavers with joints approximately 1/8 in. (3mm).
4. Where required, cut pavers with an approved cutting device to fit accurately, neatly and without damaging edges.
5. Tamp pavers with a plate compactor, uniformly level, true to grade and free of movement.
6. Spread sand to 1/8 inch (3mm) thickness over entire paving area.
7. Make one more pass with plate compactor to fill joints with sand.

Complete installation and specification details are available by contacting your Oberfields Sales Representative.

PACKAGING INFO

PRODUCT	WEIGHT PER SQ. FT.	UNITS PER SQ. FT.	UNITS PER BAND	UNITS PER CUBE	WEIGHT PER CUBE	SQ. FT. PER UNIT	SQ. FT. PER BAND	SQ. FT. PER CUBE	COLORS STOCKED
Dimensional Flagstone	24.0	N/A	N/A	48	2350	N/A	98		Bluestone, Cuyahoga, Scioto

614-252-0955
937-885-3711
800-845-7644

Fax 740-363-7644
www.oberfields.com

