Grout Sealer

Section 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: Grout Sealer

Product Number: F3526 **Product Use:** Sealant.

Manufacturer/Supplier: Custom Building Products

13001 Seal Beach Blvd Seal Beach, CA 90740

 Phone Number:
 (562) 598-8808

 Emergency Phone:
 (562) 598-8808

 Date of Preparation:
 September 21, 2008

Section 2: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER

CORROSIVE MATERIAL CAUSES BURNS.

Potential Health Effects: See Section 11 for more information.

Likely Routes of Exposure: Skin contact, eye contact, inhalation, and ingestion.

Eye: Causes burns.

Skin: Causes burns.

Ingestion: Causes burns. May be harmful if swallowed. May cause stomach distress,

nausea or vomiting.

Inhalation: May cause respiratory tract irritation.

Chronic Effects: Prolonged or repeated contact may dry skin and cause irritation.

Signs and Symptoms: Severe deep burns to eyes. Redness. Pain. Blisters. Serious skin burns.

Medical Conditions Aggravated By Exposure: Asthma. Allergies.

Target Organs: Skin, eyes, gastrointestinal tract, respiratory system.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Potential Environmental Effects: May cause long-term adverse effects in the aquatic environment. See Section 12 for more information.

Section 3: COMPOSITION / INFORMATION ON INGREDIENTS

IngredientCAS #Wt. %Potassium methylsilanetriolate31795-24-11 - 5

Section 4: FIRST AID MEASURES

Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15

minutes. If easy to do, remove contact lenses, if worn. Get medical attention

immediately.

Grout Sealer

Skin Contact: In case of contact, immediately flush skin with plenty of water. Remove

contaminated clothing and shoes. Wash clothing before reuse. Call a physician

if irritation develops and persists.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If

breathing is difficult, give oxygen.

Ingestion: If swallowed, do NOT induce vomiting unless directed to do so by medical

personnel. Never give anything by mouth to an unconscious person.

General Advice: In case of accident or if you feel unwell, seek medical advice immediately

(show the label or MSDS where possible).

Note to Physicians: Symptoms may not appear immediately.

Section 5: FIRE FIGHTING MEASURES

Flammability: Not flammable by WHMIS/OSHA criteria.

Means of Extinction:

Suitable Extinguishing Media: Powder, water spray, foam, carbon dioxide.

Unsuitable Extinguishing Media: Not available.

Products of Combustion: May include, and are not limited to: oxides of carbon.

Explosion Data:

Sensitivity to Mechanical Impact: Not available.

Sensitivity to Static Discharge: Not available.

Protection of Firefighters: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker

gear) and respiratory protection (SCBA).

Section 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental Precautions: Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

Methods for Containment: Contain and/or absorb spill, then place in a suitable container.

Methods for Clean-Up: Soak into absorbent material. Spills of this material are a slipping

hazard. Thoroughly wash the area with water after a spill or leak.

Other Information: Not available.

Section 7: HANDLING AND STORAGE

Handling:

Avoid contact with skin and eyes. Do not swallow. Do not breathe gas/fumes/vapor/spray. Handle and open container with care. When using, do not eat or drink. Wash hands before eating, drinking, or smoking.

Storage:

Keep out of the reach of children. Keep container tightly closed. Store in a cool place.

Grout Sealer

Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Exposure Limits

IngredientOSHA-PELACGIH-TLVPotassium methylsilanetriolateNot available.Not available.

Engineering Controls: Use ventilation adequate to keep exposures (airborne levels of dust,

fume, vapor, etc.) below recommended exposure limits.

Personal Protective Equipment:

Eye/Face Protection: Wear eye/face protection.

Hand Protection: Wear suitable gloves.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: In case of insufficient ventilation, wear suitable respiratory

equipment.

General Hygiene Considerations: Handle according to established industrial hygiene and

safety practices.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Opaque.

Color: White.

Odour: Low odor.

Odour Threshold: Not available.

Physical State: Liquid. pH: 12.5

Viscosity: Not available.

Freezing Point: Not available.

Boiling Point: $\sim 100^{\circ} (\sim 212^{\circ})$

Flash Point:

Evaporation Rate:

Not available.

Lower Flammability Limit:

Not available.

Vapor Pressure:

Not available.

Not available.

Not available.

Not available.

Not available.

Specific Gravity: 1.0

Solubility in Water: Miscible.

Coefficient of Water/Oil Distribution: Not available.

Auto-ignition Temperature: Not available.

Percent Volatile, wt. %: 98
VOC content, wt. %: 0

Grout Sealer

Section 10: STABILITY AND REACTIVITY

Stability: Stable under normal storage conditions.

Conditions of Reactivity: Heat. Incompatible materials.

Incompatible Materials: Acids. Aluminum.

Hazardous Decomposition Products: May include, and are not limited to: oxides of carbon. **Possibility of Hazardous Reactions:** No dangerous reaction known under conditions of

normal use.

Section 11: TOXICOLOGY INFORMATION

EFFECTS OF ACUTE EXPOSURE

Component Analysis

IngredientLD50 (oral)LC50Potassium methylsilanetriolateNot available.Not available.

Eye: Causes burns. Severe deep burns to eyes.

Skin: Causes burns. Redness. Pain. Blisters. Serious skin burns.

Ingestion: Causes burns. May be harmful if swallowed. May cause stomach distress,

nausea or vomiting.

Inhalation: May cause respiratory tract irritation.

EFFECTS OF CHRONIC EXPOSURE

Target Organs: Not available.

Chronic Effects: Not hazardous by WHMIS/OSHA criteria. **Carcinogenicity:** Not hazardous by WHMIS/OSHA criteria.

Potassium methylsilanetriolate

Ingredient

Chemical Listed as Carcinogen or Potential Carcinogen * Not listed.

* See Section 15 for more information.

Mutagenicity: Not hazardous by WHMIS/OSHA criteria.

Reproductive Effects: Not hazardous by WHMIS/OSHA criteria.

Developmental Effects:

Teratogenicity: Not hazardous by WHMIS/OSHA criteria.

Embryotoxicity: Not hazardous by WHMIS/OSHA criteria.

Respiratory Sensitization: Not hazardous by WHMIS/OSHA criteria.

Skin Sensitization: Not hazardous by WHMIS/OSHA criteria.

Toxicologically Synergistic Materials: Not available.

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity: May cause long-term adverse effects in the aquatic environment.

Persistence / Degradability: Not available.

Bioaccumulation / Accumulation: Not available.

Grout Sealer

Mobility in Environment: Not available.

Section 13: DISPOSAL CONSIDERATIONS

Disposal Instructions:

This material must be disposed of in accordance with all local, state, provincial, and federal regulations.

Section 14: TRANSPORTATION INFORMATION

DOT Classification

Not regulated.

TDG Classification

Not regulated.

Section 15: REGULATORY INFORMATION

Federal Regulations

Canadian: This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

US: MSDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200).

SARA Title III

Ingredient	Section 302	Section 304	CERCLA	Section
	(EHS) TPQ (lbs.)	EHS RQ (lbs.)	RQ (lbs.)	313
Potassium methylsilanetriolate	Not listed.	Not listed.	Not listed.	Not listed.

State Regulations

California Proposition 65:

This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

Global Inventories

Ingredient	Canada	USA
_	DSL/NDSL	TSCA
Potassium methylsilanetriolate	DSL	Yes.

HMIS - Hazardous Materials Identification System

Health - 3 Flammability - 0 Physical Hazard - 0 PPE - B

NFPA - National Fire Protection Association:

Health - 3 Fire - 0 Reactivity - 0

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

WHMIS Classification(s):

Class E - Corrosive Material

WHMIS Hazard Symbols:



Grout Sealer

SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

OSHA (O) Occupational Safety and Health Administration.

ACGIH (G) American Conference of Governmental Industrial Hygienists.

A1 - Confirmed human carcinogen. A2 - Suspected human carcinogen.

A3 - Animal carcinogen.

A4 - Not classifiable as a human carcinogen.

A5 - Not suspected as a human carcinogen.

IARC (I) International Agency for Research on Cancer.

1 - The agent (mixture) is carcinogenic to humans.

2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.

2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.

3 - The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.

4 - The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.

NTP (N) National Toxicology Program.

1 - Known to be carcinogens.

2 - Reasonably anticipated to be carcinogens.

Section 16: OTHER INFORMATION

Disclaimer:

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Expiry Date: September 21, 2011

Version #: 1.0

Prepared by: Nexreg Compliance Inc.

(519) 488-5126 www.nexreg.com