



MATERIAL SAFETY DATA SHEET

Section I

Manufacturer's Name ADDIMENT INCORPORATED

Emergency Telephone Number (404) 446-6250

Address
6555 Button Gwinnett Drive
Doraville, Georgia 30340

Chemical Name and Synonyms
Trade Name and Synonyms ADDIMENT OIL, PAINT
AND SEALER REMOVER

Chemical Family and Formula: Proprietary Information

Section II - Hazardous Ingredients

Paints, Preservatives, and Solvents	%	TLV	Alloys and Metallic Coatings	%	TLV
Pigments			Base Metal		
Catalyst			Alloys		
Vehicle			Metallic Coatings		
Solvents			Filler Metal Plus Coating or Core Flux		
Additives					
Others			Others		

Hazardous Mixtures of Other Liquids, Solids, or Gases

Naptha CAS # 64742-94-5

Section III - Physical Data

Boiling Point (°F)	N/A	Specific Gravity (H ₂ O = 1) @ 20°C	.96
Vapor Pressure (mm Hg)	N/A	% Volatile by Volume (%)	N/A
Vapor Density (AIR = 1)	N/A	Evaporation Rate	N/A

Solubility in Water Negligible

Appearance and Odor CLEAR TO WHITE LIQUID: PETROLEUM ODOR

Section IV - Fire and Explosion Hazard Data

Flash Point	UNKNOWN	Flammable Limits	UNKNOWN
-------------	---------	------------------	---------

Extinguishing Media Water fog, foam, dry chemical or carbon dioxide.

Special Fire Fighting Procedures

Wear self-contained breathing apparatus with full face piece operated in the positive pressure demand mode when fighting fires.

Unusual Fire and Explosion Hazards

Vapors are heavier than air. May travel, be ignited at remote location and flash back.

Section V - Health Hazard Data

Threshold Limit Value N/A

Effects of Overexposure Eyes: Can cause severe irritation, redness, tearing, blurred vision. Skin: Prolonged or repeated contact can cause irritation, defatting, dermatitis. Ingestion: Can cause gastrointestinal irritation, nausea, vomiting & diarrhea. Aspiration of material into lungs can cause chemical pneumonitis which can be fatal. Inhalation: excessive inhalation can cause nasal and respiratory irritation, CNS effects, and even death.

Emergency First Aid Procedures Eyes: flush with water; get immediate medical attention. Skin contact: Wash with soap and water. Remove contaminated clothing and wash before re-use. Ingestion: Do not induce vomiting. Get immediate medical attention. Inhalation: Remove to fresh air. Give artificial respiration if necessary.

Section VI - Reactivity Data

Stability	Unstable		Conditions to Avoid	
	Stable	X		None

Incompatibility (Materials to Avoid) Avoid strong oxidizing materials.

Hazardous Decomposition Products None

Hazardous Polymerization	May Occur		Conditions to Avoid	
	Will Not Occur	X		None

Section VII - Spill or Leak Procedures

Steps to be Taken in Case Material is Released or Spilled Ventilate area. Avoid breathing vapors. Eliminate all ignition sources. Use NIOSH/MSHA approved air supplied respirator. Stop spill at source. Dike area of spill and cover with absorbent material. Take care to prevent runoff. Transfer solid material to container for disposal.

Waste Disposal Method

Liquid may be disposed of by liquid incinerators: contaminated absorbent may be deposited in a landfill in accordance with all applicable federal, state, and local regulations.

Section VIII - Special Protection Information

Respiratory Protection (Specify Type)
NIOSH-approved respirator.

Ventilation	Local Exhaust	YES	Special	N/A
	Mechanical (General)	YES	Other	N/A
Protective Gloves	Neoprene, nitrile rubber		Eye Protection	Chemical Safety Goggles

Other Protective Equipment Impervious clothing and boots

Section IX - Special Precautions

Precautions to be Taken in Handling and Storing Keep containers tightly closed when not in use. Store in a dry, well-ventilated place away from sources of heat or ignition and direct sunlight. Handle with care. Do not get in eyes, on skin, or on clothing.

Other Precautions Protect from heat and flame. DOT shipping class: flammable. Protect from freezing.