

**ADDIMENT**

3	Fire Hazard	<b>HAZARD KEY</b> 4 - SEVERE 3 - SERIOUS 2 - MODERATE 1 - SLIGHT 0 - MINIMAL
2	Health Hazard	
0	Reactivity	

**MATERIAL SAFETY DATA SHEET**

Paver Seal SB

**Section I**

Manufacturer's Name:	ADDIMENT INC.	Emergency Telephone Number:	(770) 446-6250
Manufacturer's Address:	6555 Button Gwinnett Doraville, GA 30340	Chemical Name and Synonyms:	
		Trade Name and Synonyms:	Addiment Paver Seal SB
		Chemical Family and Formula:	Proprietary Information

**Section II - Hazardous Ingredients**

Paints, Preservatives, and Solvents	%	TLV	Alloys and Metallic Coatings	%	TLV
Pigments			Base Metal		
Catalyst			Alloys		
Vehicle			Metallic Coatings		
Solvents			Filler Metal Plus Coating or Core Flux		
Additives					
Others			Others		

Hazardous Mixtures of Liquids, Solids, or Gases:	%	TLV
Toluene CAS # 108883		
Xylene CAS # 1330-20-7		

**Section III - Physical Data**

Boiling Point (°F)	N/A	Specific Gravity (H <sub>2</sub> O = 1) @ 20°C	0.91
Vapor Pressure (mm Hg)	N/A	% Volatile by Volume	60%
Vapor Density (AIR = 1)	N/A	Evaporation Rate	N/A
Solubility in Water	Negligible		
Appearance and Color	Clear liquid; aromatic type odor.		

**Section IV - Fire and Explosion Hazard Data**

Flash Point	N/A	Flammable Limits	N/A
Extinguishing Media	Dry chemical, foam or carbon dioxide.		
Special Fire Fighting Procedures:	Wear self-contained breathing apparatus (pressure-demand, MSHA/NIOSH-approved or equivalent) and full protective gear. Use water spray to cool containers.		
Unusual Fire and Explosion Hazards:	Vapors heavier than air, may travel, be ignited at remote locations and flash back. Explosive air vapors mixtures may occur.		

Continued on Reverse Side

Revised 6/21/99

## Section V - Health Hazard Data

Threshold Limit Value:	100 PPM average over an 8-hr exposure (ACGIN 1987-88) 200 PPM OSHA Pel.
Effects of Overexposure:	Believed to be slight-moderate irritant to eyes with possible transient corneal injury. Slightly irritating to skin.
Inhalation can cause headache, dizziness, nausea, loss of consciousness. Prolonged contact may cause loss of appetite, nose bleeds, and liver, kidney, and CNS dysfunction.	
Emergency First Aid Procedures:	Eyes: flush with water; get immediate medical attention. Skin contact: flush area with water. Remove contaminated clothing and wash before re-use. Ingestion: do not induce vomiting. Aspiration of fluid can cause serious lung injury. Get immediate medical attention. Inhalation: remove to fresh air; apply artificial respiration if necessary.

## Section VI - Reactivity Data

Stability	Unstable	<input type="checkbox"/>	Conditions to Avoid:	Excessive heat
	Stable	XX		
Incompatibility (Materials to Avoid):	Strong oxidizers.			
Hazardous Decomposition Products:	Carbon monoxide and carbon dioxide may be formed on burning in limited air supply.			
Hazardous Polymerization	May Occur	<input type="checkbox"/>	Conditions to Avoid:	Strong oxidizers
	Will Not Occur	XX		

## Section VII - Spill or Leak Procedures

Steps to be taken in case material is released or spilled:

Eliminate all ignition sources. Ventilate area, avoid breathing vapors. Use SCBA or supplied-air mask for huge spills or in confined areas. Contain spill, dike and cover with inert material.

Transfer liquid to containers for recovery or disposal and solid material to separate container for disposal.

Waste disposal method:

Incinerate liquid and contaminated diking material at a permitted facility in accordance with all applicable federal, state and local regulations.

## Section VIII - Special Protection Information

Respiratory Protection (Specify Type):		Wear suitable MSHA/NIOSH-approved or equivalent respirator where exposure limits are exceeded		
Ventilation	Local Exhaust	Yes	Special	Explosion-proof local exhaust ventilation at point of vapor or mist release.
	Mechanical (General)	Yes	Other	N/A
Protective Gloves	Impervious	Eye Protection	Chemical splash goggles (ANSI Z87.1) or equivalent.	
Other Protective Equipment:	Rubber boots, safety shower, eyewash facility.			

## Section IX - Special Procedures

Precautions to be taken in handling and storage:

Keep container tightly closed when not in use. Ground all containers when transferring material. Transport, handle and store in accordance with OSHA Regulation 1910-106 and applicable DOT regulations.

Other Precautions:

Protect from heat and flame. Handle with care. DOT shipping class: flammable.