

ADDIMENT

| | | |
|---|---------------|---|
| 0 | Fire Hazard | HAZARD KEY 4 - SEVERE 3 - SERIOUS 2 - MODERATE 1 - SLIGHT 0 - MINIMAL |
| 0 | Health Hazard | |
| 0 | Reactivity | |

MATERIAL SAFETY DATA SHEET**Primer Seal WB****Section I**

| | | | |
|-------------------------|---|------------------------------|--------------------------------|
| Manufacturer's Name: | ADDIMENT INC. | Emergency Telephone Number: | (770) 446-6250 |
| Manufacturer's Address: | 6555 Button Gwinnett Doraville, GA 30340 | Chemical Name and Synonyms: | |
| | | Trade Name and Synonyms: | Addiment Primer Seal WB |
| | | Chemical Family and Formula: | Proprietary Information |

Section II - Hazardous Ingredients

| Paints, Preservatives, and Solvents | % | TLV | Alloys and Metallic Coatings | % | TLV |
|-------------------------------------|---|-----|--|---|-----|
| Pigments | | | Base Metal | | |
| Catalyst | | | Alloys | | |
| Vehicle | | | Metallic Coatings | | |
| Solvents | | | Filler Metal Plus Coating or Core Flux | | |
| Additives | | | | | |
| Others | | | Others | | |

| Hazardous Mixtures of Liquids, Solids, or Gases: | % | TLV |
|--|---|-----|
| None | | |
| | | |
| | | |

Section III - Physical Data

| | | | |
|-------------------------|--|--|-------------|
| Boiling Point (°F) | N/A | Specific Gravity (H ₂ O = 1) @ 20°C | 1.02 |
| Vapor Pressure (mm Hg) | N/A | % Volatile by Volume | N/A |
| Vapor Density (AIR = 1) | N/A | Evaporation Rate | N/A |
| Solubility in Water | Soluble | | |
| Appearance and Color | White milky liquid; ammonia odor. | | |

Section IV - Fire and Explosion Hazard Data

| | | | |
|-----------------------------------|--|------------------|----------------------|
| Flash Point | Non-flammable | Flammable Limits | Non-flammable |
| Extinguishing Media | Use extinguishing media appropriate for surrounding fire. | | |
| Special Fire Fighting Procedures: | None | | |

| | |
|-------------------------------------|-------------|
| Unusual Fire and Explosion Hazards: | None |
|-------------------------------------|-------------|

Section V - Health Hazard Data

| | |
|----------------------------------|---|
| Threshold Limit Value: | N/A |
| Effects of Overexposure: | Eyes: slight irritation. Skin: prolonged or repeated contact can cause irritation. Ingestion: nausea, diarrhea. Inhalation: may cause headache, nausea, irritation of nose, throat and lungs. |
| Emergency First Aid Procedures: | Eyes: flush with water. Skin contact: wash with soap and water. Ingestion: dilute with water. Consult a physician. |
| Inhalation: remove to fresh air. | |

Section VI - Reactivity Data

| | | | | |
|---------------------------------------|---|-------------------------------------|----------------------|------|
| Stability | Unstable | <input type="checkbox"/> | Conditions to Avoid: | None |
| | Stable | <input checked="" type="checkbox"/> | | |
| Incompatibility (Materials to Avoid): | None known | | | |
| Hazardous Decomposition Products: | Thermal decomposition may yield acrylic monomers. | | | |
| Hazardous Polymerization | May Occur | <input type="checkbox"/> | Conditions to Avoid: | None |
| | Will Not Occur | <input checked="" type="checkbox"/> | | |

Section VII - Spill or Leak Procedures

Steps to be taken in case material is released or spilled:
Stop spill at source. Contain spills with inert material. Transfer liquids and solid diking materials to separate containers for recovery or disposal.

Waste disposal method:
Dispose of in accordance with all applicable federal, state and local regulations.

Section VIII - Special Protection Information

| | | | | |
|--|--|-----|----------------|-------------------------|
| Respiratory Protection (Specify Type): | None required if airborne concentrations are maintained at low | | | |
| Ventilation | Local Exhaust | Yes | Special | N/A |
| | Mechanical (General) | Yes | Other | N/A |
| Protective Gloves | Neoprene | | Eye Protection | Chemical safety goggles |
| Other Protective Equipment: | None | | | |

Section IX - Special Procedures

Precautions to be taken in handling and storage:
Keep from freezing. Protect from heat and flame.

Other Precautions:
None