



The "jack of all trades" the face-mix Unity® paver can be installed alone for a classic, tailored look or used as accents or edging stones. Manufactured in a herringbone pattern to accommodate mechanical equipment for efficient machine laid applications.






UNITY





PRODUCT SPECS


a) Unity Paver – 4" × 8" All Unity pavers are 2³/4" thick Stocked in Rough Texture only Other textures available as special order are: Hammered, Smooth, Tumbled




APPLICATIONS


Pedestrian or light vehicular traffic, residential driveways, commercial applications, patios, borders and swimming pool decks.

PATTERNS





45° Herringbone




90° Herringbone

Running Bond

Basketweave

Note: Pavers can be installed on their own as machine-layable pavers.

LAYER CONFIGURATION:



Note: 4×4 fillers (see black squares in illustration) are used to keep the integrity of a layer when placed by a machine. They are no charge and not sold separately. If 4×4 fillers are used in a pattern and more are needed, installers can cut 4×8 pavers in half and install where needed.

PACKAGING INFO

PRODUCT	SF _{PER} LAYER	LAYERS PER CUBE	WT PER CUBE	SF _{PER} CUBE	COLORS STOCKED
Unity	11	8	2996	88	Rough Texture: Homecoming, Reflection, Vision

Note: Due to variations in printing, color selections should always be chosen from actual product samples.

Textured paver and patio stone surfaces require a buffer between the plate compactor and the paver surface to prevent scuffing.

COLORS Shown in rough texture





