



BASIC USES AND FEATURES

- Ideal for parks, recreational areas and streetscapes.
- · For maximum resistance to weather and vandalism.

COMPOSITION & MATERIALS

- Concrete: Air entrained, achieving 5000 PSI compressive strength in 28 days.
- Reinforcing: Steel rebars in all concrete components.
- Threaded Inserts and Machine Screws: Corrosion resistant.

AVAILABLE FINISHES

- Exposed Aggregate #1, Gray crushed limestone, 3/8" top size. (Bench #1 & #2)
- \bullet Exposed Aggregate #2, Pea gravel, 1/2" top size. (Bench #1 & #2) & #2)
- Light Sandblast Texture, natural concrete color. (Bench #1, #2, & #3)
- Smooth As-cast surfaces, natural concrete color. (Bench #1 & #2)
- Colored Precast "PC" finishes available with light sandblast texture.



800.845.7644

PRECAST CONCRETE FINISHES





Exposed Aggregate #1 Gray Crushed Limesone 3/8" Top Size



Exposed Aggregate #2 Pea Gravel 1/2" Top Size



Cuyahoga Blend



Light Sandblast Texture Natural Concrete Color



Smooth As-Cast Surface Natural Concrete Color



Scioto Blend



Buff PC201



Charcoal PC202



Light Buff PC215

NOTES:

- Available Finishes for precast concrete products are shown and described to indicate approximate color and texture involved.
- Photographic representation of finish texture is approximately 25 percent of actual size.
- Refer to Oberfields LLC® data sheets showing specific precast concrete products to see which finishes are applicable for those products.
- All Colored Precast "PC" finishes are only available in Light Sandblast texture.

